


BLOOD PRESSURE MONITOR



Model 0600

GET STARTED: greatergoods.com/0600



CUSTOMER SUPPORT

Email: info@greatergoods.com Phone: (866) 991-8494 Website: greatergoods.com

Table of Contents

IMPORTANT SAFETY INFORMATION p. 2

INTRODUCTION p. 3

DEVICE p. 4-5

SETTING TIME, DATE, AND MEASUREMENTS p. 6

TAKING MEASUREMENTS p. 7-8

MEMORY/MANAGING RECORDS p. 9-10

TIPS/MAINTENANCE p. 11

ABOUT BLOOD PRESSURE p. 12-14

TROUBLESHOOTING p. 15

DEVICE SPECIFICATIONS p. 16

COMPLIED STANDARDS LIST, FCC STATEMENT, EMC GUIDANCE p. 17

WARRANTY **p. 18**

\bigwedge	Symbol for "CAUTION" - These notes must be observed to prevent any damage to the		Symbol for "TYPE BF APPLIED PARTS"
device.		6	Symbol for "THE OPERATION GUIDE MUST BE READ"
<u> </u>	Symbol for "MANUFACTURER"		
SN	Symbol for "SERIAL NUMBER"	X	Symbol for "ENVIRONMENT PROTECTION" - Waste electrical products should not be disposed
===	Symbol for "DIRECT CURRENT"		of with household waste. Please recycle where facilities exist. Check
	Symbol for "MANUFACTURE DATE"		with your local authority or retailer for recycling advice.

Safety/Caution Information

- Consult your physician before measuring blood pressure, especially if you have any of the following conditions: hypertension, diabetes, arteriosclerosis, kidney or vascular disease, or any conditions affecting circulation.
- Do not change medication use or dosage based on measurement from this device.
 Take medication as prescribed by your physician. Only a physician is qualified to diagnose and treat high blood pressure.
- This device is not intended to be a diagnostic device.
- This device is intended for adult use only. Keep the unit out of reach of infants, children, or pets.
- This device is not intended for use on extremities other than the arm or for functions other than obtaining a blood pressure measurement. Do not use this device for any other purpose.
- Do not confuse self-monitoring with self-diagnosis. If you are taking medication, consult your physician to determine the most appropriate time to measure your blood pressure.
- If the cuff pressure exceeds 40 kPa (300 mmHg), the unit will automatically deflate.
 Should the cuff not deflate when pressures exceeds 40 kPa (300 mmHg), detach the cuff from the arm and press the START/STOP button to stop inflation.
- The equipment is not AP/APG equipment and not suitable for use in the presence of a flammable anesthetic mixture with air of with oxygen or nitrous oxide.
- Do not touch battery output and the patient simultaneously.
- Avoid strong electromagnetic field radiated interference signals or electrical fast transient/burst signals.
- This device is contraindicated for any female who may be suspected of, or is pregnant.
 Besides provided inaccurate readings, the affects of this device on the fetus are unknown.
- This unit is not suitable for continuous monitoring during medical emergencies or operations.
- Do not disassemble or attempt to repair this device or any of its components. Doing so
 will void the warranty.
- Do not use this device near flammable gasses (anesthetic gas, oxygen, hydrogen) or flammable liquids (alcohol) are present.
- Use only BALANCE™ authorized parts and accessories. Parts and accessories not approved for use with this device may damage the unit.

Introduction

Welcome to your new Balance Blood Pressure Monitor. We have designed this monitor to be as user friendly as possible to ensure that you can use it with ease.

This model detects your blood pressure measurement by using the oscillometric method, which turns your blood pressure into a digital reading. With the oscillometric method, no stethoscope is needed. The model also features blood pressure measurement, pulse rate measurement, a two-user mode, 60-entry memory storage, and a backlit LCD display for easy readability.

Please read the manual thoroughly before using this product.

OUR PROMISE

We're committed to creating 5-star products.

If we haven't delivered on our promise, please contact us.

For the best possible experience with your product,

please visit greatergoods.com/0600.




Device



SYMBOL	DESCRIPTION	EXPLANATION
SYS	Systolic blood pressure	High pressure result
DIA	Diastolic blood pressure	Low pressure result
■ kPa	kPa (kiloPascal)	Measurement unit of blood pressure
■ mmHg	mmHg (millimetres of mercury)	Measurement unit of blood pressure
Pu l /min	Pulse per minute	Beats per minute (BPM)
W	Arrhythmia	Irregular heartbeat
1	Grade	Displays grade of blood pressure
Lo+ 🗖	Low batteries	Batteries are low and need to be replaced
BB BB	Memory	The displayed measurement values is from the memory feature
м 88:88	Current time	Month/Day/Year – Hour/Minute
▼	Deflating	Cuff air is exhausting of deflating
USER 12	User ID	Start measurement and save the results for USER 1 or USER 2

Device (cont.)



Installing and Replacing the Batteries

1. Open battery cover.

2. Install the batteries by matching the correct polarity, as shown.

*Always use AAA batteries.

3. Close the cover.

Replace the batteries whenever $\frac{1}{2} = 1$ shows, the display dims, or when the display does not light up.




- . Remove batteries if the device is not likely to be used for some time.
- The old battery is harmful to the environment. Do not dispose with other daily trash.
- . Remove the old battery from the device and follow your local recycling guidelines.
- Do not dispose of batteries in fire. Batteries may explode or leak.

Setting Date, Time, and Measurement Unit

START

It is important to set the clock before using your blood pressure monitor, so that a time stamp can be assigned to each record that is stored in the memory.

- 1. When the display is off, hold the "Start/Stop" button for about 3 seconds to enter set up mode.
- 2. Press the "UP" arrow (MEM button) or the "DOWN" arrow (USER button) to change the year, then press the "SET" button to confirm the selection.



3. Once you select "SET," the next steps will appear on the screen as the following:




4. After setup is complete, the screen will display "done", show each of the entered settings, and turn off. The monitor is now ready to use.

Measurements

Fastening the Cuff

- Fasten the cuff on your upper arm, then position the tube off-center toward the inner side of the arm in line with the little finger.
- The cuff should be snug but not too tight. You should be able to insert one finger between the cuff and your arm.





3. Sit comfortably with your arm resting on a flat surface.

The middle of the cuff should be at the level of the right atrium of the heart. Before starting the measurement, sit comfortably with legs uncrossed, feet flat on the floor, back and arm supported.

IMPORTANT

- Resting for 5 minutes before measuring will give you the best reading.
- Wait at least 3 minutes between measurements. This allows your blood circulation to recover.
- For a meaningful comparison, try to measure under similar conditions. For example, take daily measurements at approximately the same time, position of upper arm, or as directed by a physician.

Measurements (cont.)

Starting the Measurement

- With the monitor off, press the "Start/Stop" button to turn on the monitor.
- If necessary: Toggle which user you want to measure as by pressing the "USER" button
- **3.** Press the "Start/Stop" button again. The blood pressure monitor will begin the reading and finish the entire measurement.
- **4.** Press the "Start/Stop" button to power off, otherwise the monitor will automatically turn off within 1 minute of the reading.







- 🚱 \Lambda CAUTION
- 1. When using this device, pay attention to the following situation, which may interrupt blood flow and influence blood circulation of the patient, thus causing injury to the patient: too frequent and consecutive measurements; the application of the cuff and its pressurization on any arm where intravascular access or therapy, or an arterio-venous (A-V) shunt, is present; or inflating the cuff on the arm on the side of a mastectomy.
- 2. Do not apply the cuff over a wound, otherwise it can cause further injury.
- 3. Do not inflate the cuff on the same limb to which other monitoring ME EQUIPMENT is applied because this could cause temporary loss of function of the monitoring ME EQUIPMENT.
- 4. Do not kink the connection tube. Otherwise, the cuff pressure may continuously increase, which can prevent blood flow and result in injury to the patient.

Memory

Recalling Records

- 1. When the monitor is off, press the "MEM" button.
- If necessary: Toggle which user you want to view history for by pressing "USER."
- Press "MEM" once more, and the average value of the last three records show for that user.
- 4. Continue selecting entries or hold the "MEM" button to scroll through previous records quickly. Press the "USER" button to switch back and forth between users



Understanding Records

NOTE: The date and time of the record will show alternately.





The current memory number M 5 0

The corresponding date is May 10th

PM 10:08

The corresponding time is 10:08 P.M.

Memory (cont.)

Deleting Records

- **1.** When the monitor is off, press the "MEM" button.
- Select user, then hold down the "MEM" and "Start/Stop" buttons simultaneously.
- 3. When the "Del done" screen is presented, all the records have been erased. Then, the display will turn off.

WARNING: This deletes all records.



Tips/Maintenance

Tips for Measurement

It can cause inaccuracy if the measurement is taken under the following circumstances:

- · Measuring within 1 hour of eating or drinking
- · Measuring after tea, coffee, or smoking
- Measuring within 20 minutes after taking a bath
- · Measuring when talking or moving your fingers
- · Measuring in a very cold environment
- · Measuring when needing to use the restroom

Maintenance

In order to get the best performance out of your monitor, please follow the below instructions:

- · Store monitor in a dry place
- Avoid contact with water, clean it with a dry cloth if needed
- · Do not attempt to clean the resizable cuff with water
- · Never submerge monitor or cuff in water

About Blood Pressure

What is the difference between systolic pressure and diastolic pressure?

When ventricles contract and pump blood out of the heart, the blood pressure reaches its maximum value in the cycle, which is called systolic pressure. When the ventricles relax, the blood pressure reaches its minimum value in the cycle, which is called diastolic pressure.

What is the standard blood pressure classification?

The chart below is the standard blood pressure classification by the American Heart Association (AHA).



blood discharging

This chart reflects blood pressure categories defined by the American Heart Association.			
Blood Pressure Category	Systolic mmHg (upper#)		Diastolic mmHg (lower#)
Normal	less than 120	and	less than 80
Prehypertension	120 – 139	or	80 – 89
High Blood Pressure (Hypertension) Stage 1	140 – 159	or	90 – 99
High Blood Pressure (Hypertension) Stage 2	160 or higher	or	100 or higher
Hypertensive Crisis (Emergency care needed)	Higher than 180	or	110 or higher

About Blood Pressure (cont.)

Why does my blood pressure fluctuate throughout the day?

- Individual blood pressure varies throughout the day. It is also affected by the way you fasten your cuff and your measurement position. Please make sure you measure your blood pressure under the same conditions each time you take a measurement.
- 2. Variations in the pressure can occur, due to certain medicines being taken.
- 3. Waiting at least 3 minutes between measurements is recommended.

Does it matter which arm I use when measuring?

It is acceptable to use either arm when measuring. However, to obtain the most consistent readings possible, it is suggested that you use the same arm each time you measure your blood pressure.

About Blood Pressure (cont.)

Why is the blood pressure I get from the hospital different from home?

Your blood pressure can vary throughout the day due to many factors such as weather, your emotions, exercise, etc.

When measuring your blood pressure at home, please check the following situations that could be causing a false measurement:

- · The cuff is too loose or too tight
- · The cuff is not secured properly
- · Not placing the cuff correctly around the arm
- · If you feel anxious, nervous, or are not relaxed
- · Not resting your arm correctly
- · Measuring too quickly after a previous reading

Irregular Heartbeat Detector

This Blood Pressure Monitor is equipped with an intelligent function of Irregular Heartbeat Detector (IHB). During each measurement, this equipment records the heartbeat intervals and works out the standard deviation. If the calculated value is larger than or equal to 15, this equipment will light up the IHB symbol on the screen when displaying the results.



The appearance of the IHB icon indicates that a pulse irregularity consistent with an irregular heartbeat was detected during measurement. Usually this is NOT a cause for concern. However, if the symbol appears often, we recommend you seek medical advice. Please note that the device does not replace a cardiac examination, but serves to detect pulse irregularities at an early stage.

Troubleshooting

PROBLEM	SYMPTOM	CHECK THIS	SOLUTION
No power	Display will not light up.	Batteries are exhausted	Replace with new batteries
		Batteries are inserted incorrectly	Insert the batteries correctly
Low batteries	Display is dim or La + icon is showing	Batteries are low	Replace with new batteries
	E1 shows on screen	The cuff is not secure	Refasten the cuff and then measure again
	E2 shows on screen	The cuff is too tight	Readjust cuff to a comfortable fit and measure again
	E3 shows on screen	The pressure of the cuff is excessive	Relax for a moment and then measure again
Error message	E10 or E11 shows on screen	The monitor detected motion, talking, or the pulse is too poor while measuring	Relax for a moment and then measure again
message	E20 shows on screen	The measurement process does not detect the pulse signal	Loosen the clothing on the arm and then measure again
	E21 shows on screen	The treatment of the measurement failed	Relax for a moment and then measure again
	EExx shows on screen	A calibration error occurred	Retake the measurement. If the problem persists, contact our customer service department for further assistance.

Device Specifications

Power supply	Battery powered mode: 6VDC 4×AAA batteries
Display mode	Digital LCD display with blue backlight V.A.60×40.5mm
Measurement mode	Oscillographic testing mode
Measurement range	Rated cuff pressure: 0kPa - 40kPa (0mmHg~300mmHg) Measurement pressure: 5.3kPa-30.7kPa (40mmHg-230mmHg) pulse value: (40-199) beat/minute
Accuracy	Pressure: 5°C-40°Cwithin±0.4kPa(3mmHg) pulse value:±5%
Normal working condition	Temperature:5°C to 40°C Relative humidity ≤85% Atmospheric pressure: 86kPa to 106kPa
Storage & transportation condition	Temperature:-20°C-60°C Relative Humidity 10%-93% Atmospheric Pressure: 50-106 kPa
Measurement perimeter of the upper arm	About 22cm~42cm
Net Weight	Approx.175 g(Excluding the dry cells)
External dimensions	Approx.110×110×40mm
Attachment	4×AAA batteries,user manual,storage bag
Mode of operation	Continuous operation
Degree of protection	Type BF applied part
Protection against ingress of water	IP21
Software Version	V01

WARNING: No modification of this equipment is allowed.

Standards List/FCC/EMC Guide

Complied Standards List

Risk management	ISO/EN 14971:2012 Medical devices — Application of risk management to medical devices
Labeling	ISO/EN 15223-1:2012 Medical devices. Symbols to be used with medical device labels, labelling and information to be supplied. General requirements
User manual	EN 1041: 2008 Medical equipment manufacturers to provide information
General Requirements For Safety	IEC 60601-1: 2005+A1: 2012 Medical electrical equipment - Part 1: General requirements for basic safety and essential performance
Electromagnetic compatibility	IEC/EN 60601-1-2:2007 Medical electrical equipment - Part 1-2: General requirements for basic safety and essential performance - Collateral standard:Electromagnetic compatibility - Requirements and tests
Performance requirements and Clinical Investigation	IEC 80601-2-30:2009 Medical electrical equipment- Part 2-30: Particular requirements for the basic safety and essential performance of automated non-invasive sphygmornanometers ANSI/AAMI SP10:2002/A2: 2008 Manual, electronic, or automated sphygmornanometers
Software life-cycle processes	IEC/EN 62304:2006+AC: 2008 Medical device software - Software life cycle processes

FCC Statement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

EMC Guidance

1. MEDICAL ELECTRICAL EQUIPMENT needs special precautions regarding EMC and needs to be installed and put into service according to the EMC information provided in the ACCOMPANYING DOCUMENTS.

 Wireless communications equipment such as wireless home network devices, mobile phones, cordless telephones and their base stations, and walkie-talkies can affect this equipment and should be kept at least a distance d=3, 3 ma way from the equipment.

(Note: As indicated in Table 6 of IEC 60601-1-2:2007 for ME EQUIPMENT, a typical cell phone with a maximum output power of 2 W yields d=3. 3m at an IMMUNITY LEVEL of 3V/m)

Warranty

Warranty Information

Your Blood Pressure Monitor is warranted by the manufacturer against defects in materials and workmanship for two (2) years from the original purchaser from the date of purchase. Proof of purchase is required.

The warranty is void if the product has been subjected to mechanical damage or mistreatment, such as immersion. This warranty is in lieu of all other warranties, and limits the liability of the manufacturer. This warranty gives you certain legal rights and you may have other rights depending on which state the product was purchased.

Manufactured by: Guangdong Transtek Medical Electronics Co., Ltd **Company:** Guangdong Transtek Medical Electronics Co., Ltd **Address:** Zone A, No.105, Dongli Road, Torch Development District, Zhongshan, 528437, Guangdong, China

If you have any questions about your product, please contact us.

Distributed by: Greater Goods LLC. 125 N Main St Suite 202 St Charles, MO 63301



(toll free) 866-991-8494



greatergoods.com/0600

